

View Online at <https://aerobasegroup.com/nsn/5925-00-234-0122>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.850 inches

Overall Height:

1.515 inches

Overall Width:

1.890 inches

Case Material:

Metal

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded stud

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

33.0 amperes dc third location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac first location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc third location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.055 at 200 pct all locations and 0.095 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Special Features:

Supplied with externally mtd resistor located between pole 2 term.

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0