

View Online at <https://aerobasegroup.com/nsn/5925-00-234-0122>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.850 inches

**Overall Height:**

1.515 inches

**Overall Width:**

1.890 inches

**Case Material:**

Metal

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded stud

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

33.0 amperes dc third location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac first location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 dc third location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.055 at 200 pct all locations and 0.095 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed

**Special Features:**

Supplied with externally mtd resistor located between pole 2 term.

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0