

View Online at <https://aerobasegroup.com/nsn/5925-00-236-0758>

**Body Style:**

Multipole-single actuator type

**Body Length:**

3.344 inches

**Body Width:**

3.000 inches

**Body Height:**

2.312 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

1.000 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.220 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 terminal

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

60.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

20.000 at 200 pct all locations and 60.000 at 200 pct all locations

**Inclsure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

3 clip and 3 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0