## NSN 5925-00-238-5901

Circuit Breaker - Page 1 of 2

Multipole-multiple actuator type

**Body Style:** 

0.125 inches **Body Length:** 

**Bushing Length:** 



View Online at https://aerobasegroup.com/nsn/5925-00-238-5901

| 6.000 inches   |
|--|
| Body Width:  |
| 2.750 inches   |
| Case Material:   |
| Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:  |
| 5.062 inches   |
| Center To Center Distance Between Terminals Parallel To Width:   |
| 1.375 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.188 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:   |
| 4.500 inches   |
| Fragility Factor:  |
| Moderately rugged  |
| Mounting Surface To Terminal End Distance:   |
| 3.375 inches   |
| Pole Quantity:   |
| 2  |
|  |
| Arc Quenching Method:  |
| Arc Quenching Method:  Magnetic blowout  |
| -  |
| Magnetic blowout   |
| Magnetic blowout  Mounting Facility Type And Quantity:   |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:   |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:   |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic   |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:   |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  Operating Voltage Type And Rating Per Pole In Volts:  |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  Operating Voltage Type And Rating Per Pole In Volts:  240.0 ac all locations and 250.0 dc all locations   |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  Operating Voltage Type And Rating Per Pole In Volts:  240.0 ac all locations and 250.0 dc all locations  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  Operating Voltage Type And Rating Per Pole In Volts:  240.0 ac all locations and 250.0 dc all locations  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac all locations and 5000.0 dc all locations  |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  Operating Voltage Type And Rating Per Pole In Volts:  240.0 ac all locations and 250.0 dc all locations  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac all locations and 5000.0 dc all locations  Circuit Protection Type:                            |
| Magnetic blowout  Mounting Facility Type And Quantity:  2 unthreaded hole  Storage Type:  General purpose warehouse  Special Handling Feature:  Magnetic  Maximum Continuous Load Current Rating Per Pole:  30.0 amperes ac all locations and 30.0 amperes dc all locations  Operating Voltage Type And Rating Per Pole In Volts:  240.0 ac all locations and 250.0 dc all locations  Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:  10000.0 ac all locations and 5000.0 dc all locations  Circuit Protection Type:  Overcurrent all locations |

## **NSN 5925-00-238-5901** Circuit Breaker - Page 2 of 2



| Trip Release Characteristic:   |
|--|
| Time delay all locations   |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 all locations  |
| Reset Method:  |
| Manual   |
| Main Contact Tripping Mechanism Type:                                  |
| Trip free  |
| Manual Actuator Type And Quantity:                                     |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole two  |
| Trip Delay Time In Seconds Per Rated Continuous Current:               |
| 30.000 at 200 pct all locations and 85.000 at 200 pct all locations    |
| Inclosure Protection Type For Which Designed:                          |
| Dustproof and general purpose and fungus resistant                     |
| Trip Release Ambient Tempurature Rating:                               |
| 40.0 degrees celsius all locations                                     |
| Frequency In Hertz:  |
| 60.0 all locations   |
| Unpackaged Unit Weight:  |
| 3.000 pounds   |
| Terminal Type And Quantity:  |
| 4 compression  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |
|  |
|  |