NSN 5925-00-244-4410

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-244-4410 **Overall Length:** 2.063 inches **Overall Height:** 2.875 inches **Overall Width:** 0.750 inches **Case Material: Plastic** Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.813 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1500.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Reset

1 toggle

Actuator Fun

Reset

Thread Size:
0.138 inches

NSN 5925-00-244-4410

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

1200.000 at 125 pct single location and 2.800 at 400 pct single location

Trip Release Ambient Tempurature Rating:

75.0 degrees celsius single location

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0