## NSN 5925-00-244-7359



Circuit Breaker Tripper - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5925-00-244-7359 **Body Style:** Rectangular dimensional envelope **Overall Length:** 7.750 inches **Overall Height:** 4.250 inches **Overall Width:** 4.750 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 terminal **Maximum Continuous Load Current Rating Per Pole:** 400.0 amperes ac all locations and 400.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 200.0 all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 600.000 at 200 pct all locations and 1440.000 at 200 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 6 screw Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A030a0