NSN 5925-00-245-3391

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-245-3391 **Body Style:** Multipole-multiple actuator type **Body Length:** 2.530 inches **Body Width:** 1.530 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.940 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.060 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.750 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.150 inches **Mounting Surface To Terminal End Distance:** 2.630 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 200.0 milliamperes dc first location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 dc first location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3000.0 dc first location **Circuit Protection Type:**

Trip Release Method:

Overcurrent all locations

Magnetic-hydraulic all locations

NSN 5925-00-245-3391 Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay second location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Shunt trip second location
Thread Size:
0.190 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 200 pct second location and 10.000 at 200 pct second location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 second location
Thread Series Designator:
Unc
Terminal Type And Quantity:
7 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0