NSN 5925-00-245-3391

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-245-3391

Body Style:

Multipole-multiple actuator type

Body Length:

2.530 inches

Body Width:

1.530 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

2.630 inches

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

200.0 milliamperes dc first location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc first location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3000.0 dc first location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-00-245-3391

Circuit Breaker - Page 2 of 2



Trip Release Characteristic: Time delay second location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 115.0 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 2 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One and two linked Internal Trip Release Configuration: Shunt trip second location **Thread Size:** 0.190 inches Trip Delay Time In Seconds Per Rated Continuous Current: 4.000 at 200 pct second location and 10.000 at 200 pct second location **Inclosure Protection Type For Which Designed:** Fungus resistant and moisture resistant Frequency In Hertz: 60.0 second location **Thread Series Designator:** Unc **Terminal Type And Quantity:** 7 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0