NSN 5925-00-247-8567

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-247-8567 **Body Style:** Single pole type **Body Length:** 2.189 inches **Body Width:** 0.500 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.188 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.812 inches **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location and 5.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location and 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3000.0 ac single location and 5000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 single location **Ultimate Trip Time Per Pole In Seconds:** 300.000 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

Manual Actuator Type And Quantity: 1 toggle

NSN 5925-00-247-8567 Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
20.000 at 200 pct single location and 80.000 at 200 pct single location
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Special Features:
Refinish mtg face plate the sides and top surface of the handle bezel
Frequency In Hertz:
400.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0