

View Online at <https://aerobasegroup.com/nsn/5925-00-248-1377>

Body Style:

Rectangular dimensional envelope

Overall Length:

7.750 inches

Overall Height:

4.250 inches

Overall Width:

4.750 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 terminal

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

600.0 amperes ac all locations and 600.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+1800.0/+2100.0 ac all locations and +1800.0/+2100.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

5400.000 at 150 pct all locations and 600.000 at 200 pct all locations and 1440.000 at 200 pct all locations and 120.000 at 300 pct all locations and 450.000 at 300 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0