NSN 5925-00-248-1382

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-248-1382

Body Style:

Rectangular dimensional envelope

Overall Length:

8.469 inches

Overall Height:

3.109 inches

Overall Width:

4.844 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 terminal

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations and 400.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+1800.0/+2100.0 ac all locations and +1800.0/+2100.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

120.000 at 300 pct all locations and 300.000 at 300 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5925-00-248-1382

Circuit Breaker Tripper - Page 2 of 2

Fiig: A030a0

