

View Online at <https://aerobasegroup.com/nsn/5925-00-248-1410>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

8.469 inches

**Overall Height:**

3.109 inches

**Overall Width:**

3.891 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 terminal

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

175.0 amperes ac all locations and 175.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations and 250.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

200.0 all locations

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+2100.0/+2450.0 ac all locations and +2100.0/+2450.0 dc all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5400.000 at 150 pct all locations and 150.000 at 300 pct all locations and 420.000 at 300 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0