# NSN 5925-00-248-1416

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-248-1416

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

8.469 inches

## **Overall Height:**

3.109 inches

**Overall Width:** 

3.891 inches

**Pole Quantity:** 

3

#### Mounting Facility Type And Quantity:

6 terminal

Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac all locations and 150.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

500.0 ac all locations and 250.0 dc all locations

# Circuit Protection Type:

Overcurrent all locations

### Trip Release Method:

Thermal-magnetic all locations

**Trip Release Characteristic:** 

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

#### Adjustable Trip Setting Current Range Per Pole In Amps:

+1800.0/+2100.0 ac all locations and +1800.0/+2100.0 dc all locations

#### Trip Delay Time In Seconds Per Rated Continuous Current:

150.000 at 300 pct all locations and 420.000 at 300 pct all locations

#### Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

#### **Frequency In Hertz:**

60.0 all locations

## **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5925-00-248-1416

Circuit Breaker Tripper - Page 2 of 2

Fiig: A030a0

