

View Online at <https://aerobasegroup.com/nsn/5925-00-248-1422>

Body Style:

Rectangular dimensional envelope

Overall Length:

8.469 inches

Overall Height:

3.109 inches

Overall Width:

3.891 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

Terminal

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations and 125.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+1500.0/+1750.0 ac all locations and +1500.0/+1750.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

5400.000 at 150 pct all locations and 150.000 at 300 pct all locations and 420.000 at 300 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0