## NSN 5925-00-248-1429

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-248-1429 **Body Style:** Rectangular dimensional envelope **Overall Length:** 5.625 inches **Overall Height:** 3.750 inches **Overall Width:** 4.500 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 200.0 all locations Adjustable Trip Setting Current Range Per Pole In Amps: +600.0/+700.0 ac all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 5400.000 at 150 pct all locations and 600.000 at 200 pct all locations and 1440.000 at 200 pct all locations and 120.000 at 300 pct all locations and 450.000 at 300 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 6 screw Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5925-00-248-1429

Circuit Breaker Tripper - Page 2 of 2



Fiig:

A030a0