# NSN 5925-00-248-1430

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-248-1430

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

4.594 inches

# **Overall Height:**

3.531 inches

#### **Overall Width:**

3.844 inches

**Pole Quantity:** 

3

#### Mounting Facility Type And Quantity:

6 terminal

#### Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

# **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

175.0 all locations

#### Adjustable Trip Setting Current Range Per Pole In Amps:

+1200.0/+1400.0 ac all locations

#### Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 150 pct all locations and 420.000 at 200 pct all locations and 1500.000 at 200 pct all locations and 120.000 at 300 pct all locations

#### **Trip Release Ambient Tempurature Rating:**

50.0 degrees celsius all locations

# Frequency In Hertz:

60.0 all locations

#### **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5925-00-248-1430

Circuit Breaker Tripper - Page 2 of 2

Fiig: A030a0

