# NSN 5925-00-248-1438

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-248-1438

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

4.594 inches

### **Overall Height:**

3.531 inches

#### **Overall Width:**

3.844 inches

**Pole Quantity:** 

3

#### Mounting Facility Type And Quantity:

6 terminal

#### Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

75.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

### Trip Release Method:

Thermal-magnetic all locations

### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

175.0 all locations

#### Adjustable Trip Setting Current Range Per Pole In Amps:

+900.0/+1050.0 ac all locations

#### Trip Delay Time In Seconds Per Rated Continuous Current:

420.000 at 200 pct all locations and 1500.000 at 200 pct all locations

#### **Trip Release Ambient Tempurature Rating:**

50.0 degrees celsius all locations

#### **Frequency In Hertz:**

60.0 all locations

#### **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

# NSN 5925-00-248-1438

Circuit Breaker Tripper - Page 2 of 2

Fiig: A030a0

