## NSN 5925-00-248-4331



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-248-4331 **Body Length:** 3.281 inches **Body Width:** 3.000 inches **Body Height:** 2.359 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.140 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 40.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 2 toggle

**Actuator Function:** 

Trip-reset

## NSN 5925-00-248-4331

Circuit Breaker - Page 2 of 2

Fiig: A030a0



Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Trip Delay Time In Seconds Per Rated Continuous Current:
18.000 at 200 pct all locations and 125.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No