

View Online at <https://aerobasegroup.com/nsn/5925-00-250-4372>

**Body Style:**

Multipole-single actuator type

**Overall Length:**

5.250 inches

**Overall Height:**

2.000 inches

**Overall Width:**

2.688 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

35.000 at 200 pct all locations and 130.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

1.250 pounds

**Terminal Type And Quantity:**

4 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0