

View Online at <https://aerobasegroup.com/nsn/5925-00-250-8143>

Overall Length:

2.125 inches

Overall Height:

2.875 inches

Overall Width:

0.750 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

21.000 at 200 pct single location and 2.500 at 500 pct single location

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit single location

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0