NSN 5925-00-251-3283

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-251-3283

Body Style:
Single pole type
Bushing Length:
0.375 inches
Body Length:
1.375 inches
Body Width:
0.687 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.020 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
2.035 inches
Pole Quantity:
1
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 threaded bushing
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
24
Maximum Continuous Load Current Rating Per Pole:
30.0 amperes ac single location and 30.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location and 50.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac single location and 1000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
135.0 single location
Reset Method:

Manual

NSN 5925-00-251-3283 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
6.000 at 200 pct single location and 20.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Humidity resistant and salt spray proof and shock resistant and vibration resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
2.000 ounces
Thread Series Designator:
Unf
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0