## NSN 5925-00-252-8214



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-252-8214 **Body Style:** Rectangular dimensional envelope **Overall Length:** 5.500 inches **Overall Height:** 3.594 inches **Overall Width:** 4.500 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 all locations **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two **Trip Delay Time In Seconds Per Rated Continuous Current:** 25.000 at 500 pct all locations and 40.000 at 500 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

N/a

## NSN 5925-00-252-8214

Circuit Breaker Tripper - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A030a0