

View Online at <https://aerobasegroup.com/nsn/5925-00-254-2672>

Overall Length:

2.188 inches

Overall Height:

2.406 inches

Overall Width:

0.750 inches

Pole Quantity:

1

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

100.000 at 200 pct single location and 10.000 at 400 pct single location and 3600.000 at 138 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0