NSN 5925-00-254-4924



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-254-4924 **Body Style:** Rectangular dimensional envelope **Overall Length:** 8.469 inches **Overall Height:** 3.109 inches **Overall Width:** 3.891 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 150.0 amperes ac all locations and 150.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 200.0 all locations Adjustable Trip Setting Current Range Per Pole In Amps: +900.0/+1050.0 ac all locations and +900.0/+1050.0 dc all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 5400.000 at 150 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 6 screw Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5925-00-254-4924Circuit Breaker Tripper - Page 2 of 2



Fiig:

A030a0