

View Online at <https://aerobasegroup.com/nsn/5925-00-257-5731>

Body Style:

Rectangular dimensional envelope

Overall Length:

23.875 inches

Overall Height:

14.000 inches

Overall Width:

14.375 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.562 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

320.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

1000.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

156.0 all locations

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 rotary

Internal Trip Release Configuration:

Shunt trip all locations

Terminal Type And Quantity:

4 bus bar

Reference Number Differentiating Characteristics:

As differentiated by continuous load current per pole, ultimate trip rating of continuous current rating per pole in percent

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0