NSN 5925-00-257-7066

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-7066 **Overall Length:** 2.500 inches **Overall Height:** 3.172 inches Overall Width: 0.750 inches **Case Material: Plastic Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 500.0 milliamperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 125.0 ac single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 2000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 single location **Reset Method:** Automatic **Thread Size:** 0.138 inches **Trip Delay Time In Seconds Per Rated Continuous Current:** 6.000 at 125 pct single location and 22.000 at 125 pct single location and 2.500 at 200 pct single location and 7.500 at 200 pct single location and 0.800 at 300 pct single location and 2.500 at 300 pct single location **Inclosure Protection Type For Which Designed:** Moisture resistant and shockproof and vibrationproof Frequency In Hertz: 60.0 single location

Thread Series Designator:

Unc **Terminal Type And Quantity:**

2 threaded stud

NSN 5925-00-257-7066

Circuit Breaker - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0