

View Online at <https://aerobasegroup.com/nsn/5925-00-257-7066>

Overall Length:

2.500 inches

Overall Height:

3.172 inches

Overall Width:

0.750 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

500.0 milliamperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Automatic

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 125 pct single location and 22.000 at 125 pct single location and 2.500 at 200 pct single location and 7.500 at 200 pct single location and 0.800 at 300 pct single location and 2.500 at 300 pct single location

Inclosure Protection Type For Which Designed:

Moisture resistant and shockproof and vibrationproof

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0