

View Online at <https://aerobasegroup.com/nsn/5925-00-257-7072>

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.266 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

180.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Automatic

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip w/dual rating and remote trip feature single location

Trip Delay Time In Seconds Per Rated Continuous Current:

50.000 at 250 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0