

View Online at <https://aerobasegroup.com/nsn/5925-00-257-8743>

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations and 15.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations and 5000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

120.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Trip Delay Time In Seconds Per Rated Continuous Current:**

27.000 at 200 pct all locations and 100.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0