

View Online at <https://aerobasegroup.com/nsn/5925-00-257-9109>

Body Style:

Rectangular dimensional envelope

Overall Length:

8.438 inches

Overall Height:

4.250 inches

Overall Width:

4.625 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 terminal

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

250.0 amperes ac all locations and 250.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Adjustable Trip Setting Current Range Per Pole In Amps:

+650.0/+1300.0 ac all locations and +650.0/+1300.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 150 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A030a0