NSN 5925-00-257-9110

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-9110

Body Style:
Rectangular dimensional envelope
Overall Length:
8.438 inches
Overall Height:
4.250 inches
Overall Width:
4.625 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 terminal
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
250.0 amperes ac all locations and 250.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations and 250.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
Adjustable Trip Setting Current Range Per Pole In Amps:
+1500.0/+3000.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
3600.000 at 150 pct all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:

6 screw

NSN 5925-00-257-9110

Circuit Breaker Tripper - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0