## NSN 5925-00-257-9111

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-9111

Body Style:		
Rectangular dimensional envelope		
Overall Length:		
8.438 inches		
Overall Height:		
4.250 inches		
Overall Width:		
4.625 inches		
Pole Quantity:		
3		
Mounting Facility Type And Quantity:		
6 terminal		
Features Provided:		
Adjustable trip release		
Maximum Continuous Load Current Rating Per Pole:		
225.0 amperes ac all locations and 225.0 amperes dc all locations		
Operating Voltage Type And Rating Per Pole In Volts:		
500.0 ac all locations and 250.0 dc all locations		
Circuit Protection Type:		
Overcurrent all locations		
Trip Release Method:		
Thermal-magnetic all locations		
Trip Release Characteristic:		
Instantaneous all locations and time delay all locations		
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:		
150.0 all locations		
Manual Actuator Type And Quantity:		
1 toggle		
Actuator Function:		
Trip-reset		
Actuator Position Designation:		
At each pole		
Adjustable Trip Setting Current Range Per Pole In Amps:		
+650.0/+1300.0 ac all locations and +650.0/+1300.0 dc all locations		
Trip Delay Time In Seconds Per Rated Continuous Current:		
3600.000 at 150 pct all locations		
Trip Release Ambient Tempurature Rating:		
50.0 degrees celsius all locations		
Frequency In Hertz:		
60.0 all locations		
Terminal Type And Quantity:		

6 screw

## NSN 5925-00-257-9111

Circuit Breaker Tripper - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0