NSN 5925-00-257-9114

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-9114

Body Style:

Rectangular dimensional envelope

Overall Length:

11.000 inches

Overall Height:

6.000 inches

Overall Width:

9.000 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 terminal

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac all locations and 150.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+1950.0/+3900.0 ac all locations and +2250.0/+4100.0 dc all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-257-9114

Circuit Breaker Tripper - Page 2 of 2

Frequency In Hertz: 60.0 all locations Unpackaged Unit Weight: 4.000 pounds Precious Material And Location: Contacts silver Precious Material: Silver Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0

