NSN 5925-00-257-9116



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-257-9116 **Body Style:** Rectangular dimensional envelope **Overall Length:** 8.438 inches **Overall Height:** 4.250 inches **Overall Width:** 4.625 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 250.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole Adjustable Trip Setting Current Range Per Pole In Amps: +650.0/+1300.0 dc all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 300.000 at 200 pct all locations and 900.000 at 200 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations **Terminal Type And Quantity:** 6 screw Shelf Life:

N/a

NSN 5925-00-257-9116

Circuit Breaker Tripper - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A030a0