NSN 5925-00-257-9117

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-9117

view Online at https://aerobasegroup.com/nsn/5925-00-257-9117
Body Style:
Rectangular dimensional envelope
Overall Length:
11.000 inches
Overall Height:
6.000 inches
Overall Width:
9.000 inches
Unthreaded Mounting Hole Diameter:
0.190 inches
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
160.0 amperes ac all locations and 160.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations and 250.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:

Trip Release Ambient Tempurature Rating:

+1950.0/+3900.0 ac all locations and +1950.0/+3900.0 dc all locations

50.0 degrees celsius all locations

NSN 5925-00-257-9117

Circuit Breaker Tripper - Page 2 of 2



Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.000 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0