## NSN 5925-00-257-9119

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-9119

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

8.438 inches

### **Overall Height:**

4.250 inches

**Overall Width:** 

4.625 inches

**Pole Quantity:** 

3

#### Mounting Facility Type And Quantity:

6 terminal

Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

250.0 amperes ac all locations and 250.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

500.0 ac all locations and 250.0 dc all locations

#### Circuit Protection Type:

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

## Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

## Actuator Position Designation:

At each pole

## Adjustable Trip Setting Current Range Per Pole In Amps:

+3900.0/+7800.0 ac all locations and +4000.0/+8800.0 dc all locations

## Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 150 pct all locations

## Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

## Frequency In Hertz:

60.0 all locations

## Terminal Type And Quantity:

6 screw

# NSN 5925-00-257-9119

Circuit Breaker Tripper - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

