# NSN 5925-00-257-9536

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-257-9536

## **Body Style:**

Multipole-multiple actuator type

## **Bushing Length:**

0.125 inches

# Body Length:

6.000 inches

### Body Width:

2.750 inches

#### **Case Material:**

Plastic

## Center To Center Distance Between Terminals Parallel To Length:

## 5.062 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.375 inches

**Unthreaded Mounting Hole Diameter:** 

## 0.188 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.500 inches

# **Fragility Factor:**

Moderately rugged

## Mounting Surface To Terminal End Distance:

3.375 inches

## Pole Quantity:

2

# Arc Quenching Method:

Magnetic blowout

# Mounting Facility Type And Quantity:

2 unthreaded hole

# Storage Type:

General purpose warehouse

# Special Handling Feature:

Magnetic

# Maximum Continuous Load Current Rating Per Pole:

70.0 amperes ac all locations and 70.0 amperes dc all locations

# Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 250.0 dc all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 5000.0 dc all locations

# Circuit Protection Type:

Overcurrent all locations

# Trip Release Method:

Thermal-magnetic all locations

# NSN 5925-00-257-9536

Circuit Breaker - Page 2 of 2



# Trip Release Characteristic:

Time delay all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# **Reset Method:**

Manual

## Main Contact Tripping Mechanism Type:

Trip free

## Manual Actuator Type And Quantity:

1 toggle

# Actuator Function:

Trip-reset

## Actuator Position Designation:

At pole two

#### Trip Delay Time In Seconds Per Rated Continuous Current:

85.000 at 200 pct all locations and 240.000 at 200 pct all locations

## Inclosure Protection Type For Which Designed:

Dustproof and general purpose and fungus resistant

## **Trip Release Ambient Tempurature Rating:**

50.0 degrees celsius all locations

## Frequency In Hertz:

60.0 all locations

#### **Unpackaged Unit Weight:**

3.000 pounds

# Terminal Type And Quantity:

4 compression

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A030a0