## NSN 5925-00-258-1973

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-258-1973 **Overall Length:** 5.125 inches **Overall Height:** 5.875 inches **Overall Width:** 1.500 inches **Case Material: Plastic Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 115.0 ac single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 3000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Automatic **Thread Size:** 0.164 inches **Trip Delay Time In Seconds Per Rated Continuous Current:** 3.600 at 125 pct single location and 6.000 at 125 pct single location and 1.000 at 200 pct single location and 1.700 at 200 pct single location and 0.400 at 300 pct single location and 0.620 at 300 pct single location Frequency In Hertz: 60.0 single location **Thread Series Designator:** Unc

N/a

2 threaded stud Shelf Life:

**Terminal Type And Quantity:** 

## NSN 5925-00-258-1973

Circuit Breaker - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A030a0