NSN 5925-00-258-4084

Circuit Breaker - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5925-00-258-4084

# Pole Quantity:

1

### Mounting Facility Type And Quantity:

2 threaded hole

### **Features Provided:**

Adjustable trip release

## Thready Qty Per Inch (tpi):

32

### Maximum Continuous Load Current Rating Per Pole:

500.0 milliamperes ac single location and 500.0 milliamperes dc single location

## Operating Voltage Type And Rating Per Pole In Volts:

230.0 ac single location and 230.0 dc single location

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

230.0 ac single location and 230.0 dc single location

## **Circuit Protection Type:**

Overcurrent single location

## Trip Release Method:

Magnetic single location

### **Reset Method:**

Manual

### Main Contact Tripping Mechanism Type:

Trip free

### Adjustable Trip Setting Current Range Per Pole In Amps:

+0.5/+2.0 ac single location and +0.5/+2.0 dc single location

#### Internal Trip Release Configuration:

Series trip single location

#### Thread Size:

0.190 inches

#### **Frequency In Hertz:**

60.0 single location

#### **Thread Series Designator:**

Unf

## Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A030a0