## NSN 5925-00-258-5048

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-258-5048 **Body Style:** Single pole type **Overall Length:** 3.156 inches **Body Width:** 1.875 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.062 inches **Unthreaded Mounting Hole Diameter:** 0.203 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.406 inches **Mounting Surface To Terminal End Distance:** 1.359 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 60.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6900.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 115.0 single location **Reset Method:** 

Automatic

**Internal Trip Release Configuration:** 

Series trip single location

## NSN 5925-00-258-5048

Circuit Breaker - Page 2 of 2



Trin	Delay	Time	In 9	Seconds	Per	Rated	Continuous	Current:
HID	Delay	HIIIIE	III (	seconus	rei	Raieu	Continuous	Current.

600.000 at 125 pct single location and 40.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:** 

Moisture proof

**Terminal Type And Quantity:** 

2 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A030a0