NSN 5925-00-258-5049



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-258-5049 **Body Style:** Rectangular dimensional envelope **Overall Length:** 5.000 inches **Overall Height:** 3.562 inches **Overall Width:** 4.312 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations and 100.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 124.0 all locations Adjustable Trip Setting Current Range Per Pole In Amps: +350.0/+1000.0 ac all locations and +350.0/+1000.0 dc all locations **Internal Trip Release Configuration:** Series trip all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 92.000 at 200 pct all locations and 400.000 at 200 pct all locations **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 4 compression Shelf Life:

N/a
Unit Of Measure:

NSN 5925-00-258-5049

Circuit Breaker Tripper - Page 2 of 2



Demilitarization:

No

Fiig:

A030a0