

View Online at <https://aerobasegroup.com/nsn/5925-00-258-8278>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

6.500 inches

**Overall Height:**

3.938 inches

**Overall Width:**

4.469 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

133.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Trip Delay Time In Seconds Per Rated Continuous Current:**

19.000 at 200 pct all locations and 110.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

70.0 degrees fahrenheit all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

3 screw and 3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0