

View Online at <https://aerobasegroup.com/nsn/5925-00-258-8497>

Overall Length:

3.330 inches

Overall Height:

2.530 inches

Overall Width:

0.760 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.020 at 125 pct single location and 6.000 at 125 pct single location and 0.250 at 200 pct single location and 0.850 at 200 pct single location and 0.090 at 300 pct single location and 3.000 at 300 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0