

View Online at <https://aerobasegroup.com/nsn/5925-00-258-8625>

Overall Length:

6.000 inches

Overall Height:

3.969 inches

Overall Width:

2.750 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

2

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 threaded hole and 3 unthreaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Thread Size:

0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

50.000 at 150 pct all locations and 40.000 at 150 pct all locations and 7.000 at 300 pct all locations and 25.000 at 300 pct all locations and 1.800 at 600 pct all locations and 5.000 at 600 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Mtg holes counterbored and spaced 1.375 and 0.938 in. From upper edge

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0