

View Online at <https://aerobasegroup.com/nsn/5925-00-258-8625>

**Overall Length:**

6.000 inches

**Overall Height:**

3.969 inches

**Overall Width:**

2.750 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 threaded hole and 3 unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip w/separate reset

**Thread Size:**

0.164 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

50.000 at 150 pct all locations and 40.000 at 150 pct all locations and 7.000 at 300 pct all locations and 25.000 at 300 pct all locations and 1.800 at 600 pct all locations and 5.000 at 600 pct all locations

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Special Features:**

Mtg holes counterbored and spaced 1.375 and 0.938 in. From upper edge

**Precious Material:**

Silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0