## NSN 5925-00-259-4616



Circuit Breaker Tripper - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-259-4616 **Body Style:** Rectangular dimensional envelope **Overall Length:** 8.500 inches **Overall Height:** 5.000 inches **Overall Width:** 6.000 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Maximum Continuous Load Current Rating Per Pole:** 300.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole **Trip Delay Time In Seconds Per Rated Continuous Current:** 3600.000 at 150 pct all locations **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations **Terminal Type And Quantity:** 6 screw Shelf Life: N/a

\_\_

**Unit Of Measure:** 

## NSN 5925-00-259-4616

Circuit Breaker Tripper - Page 2 of 2



Demilitarization:

No

Fiig:

A030a0