## NSN 5925-00-259-4789

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-259-4789

### Body Style:

Rectangular dimensional envelope

**Overall Length:** 

8.438 inches

#### **Overall Height:**

4.250 inches

**Overall Width:** 

4.625 inches

**Pole Quantity:** 

3

#### Mounting Facility Type And Quantity:

6 terminal

Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations and 125.0 amperes dc all locations

### **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations and 250.0 dc all locations

#### Circuit Protection Type:

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

## Manual Actuator Type And Quantity:

1 toggle

## Actuator Function:

Trip-reset

## Actuator Position Designation:

At each pole

## Adjustable Trip Setting Current Range Per Pole In Amps:

+1950.0/+3900.0 ac all locations and +2250.0/+4100.0 dc all locations

## Trip Delay Time In Seconds Per Rated Continuous Current:

3600.000 at 150 pct all locations

## Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

## Frequency In Hertz:

60.0 all locations

## Terminal Type And Quantity:

6 screw

# NSN 5925-00-259-4789

Circuit Breaker Tripper - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

