NSN 5925-00-259-4810



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-259-4810 **Overall Length:** 22.000 inches **Overall Height:** 7.000 inches **Overall Width:** 8.250 inches **Case Material:** Plastic Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 20.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.750 inches **Pole Quantity: Arc Quenching Method: Mounting Facility Type And Quantity:** 4 threaded stud **Maximum Continuous Load Current Rating Per Pole:** 400.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 30000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:**

Reset

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-259-4810

Circuit Breaker - Page 2 of 2



Frequency In Hertz:
60.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0