NSN 5925-00-259-4810

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-259-4810

Overall Length:

22.000 inches

Overall Height:

7.000 inches

Overall Width:

8.250 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

20.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Pole Quantity:

3

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

4 threaded stud

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

30000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-259-4810

Circuit Breaker - Page 2 of 2

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0

