

View Online at <https://aerobasegroup.com/nsn/5925-00-260-4298>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.390 inches and 0.565 inches

Body Length:

1.562 inches

Body Width:

1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Mounting Surface To Terminal End Distance:

1.828 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

250.0 milliamperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.055 at 200 pct all locations and 0.950 at 200 pct all locations and 0.240 at 400 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0